



Counter drone module

Contact person:Albert

<https://veuiu.com>

Email:fpvdrone@mail.veuiu.com

**40dB Gain,10w,CustomizableMHz
amplifier**

Solid state Broadband high power interference source

This module is a 10W solid-state broadband high-power interference source amplifier.Features built-in control and monitoring protection features to ensure high availability.This amplifier is suitable for broadband interference.

Features

Customizable MHz frequency range
Power gain 40 dB

olid-state Class AB Broadband design
Instantaneous ultra broadband
Small and lightweight
High reliability and ruggedness

ELECTRICAL SPECIFICATIONS(,DC= 28V,Load VSWR $\leq$ 1.5))

Description	Symbol	Min	Typ	Max	Unit
Operating Frequency	BW	Customizable			MHz
Output Power CW	Psat			10	W
Power Gain @ Psat	Gp		40		dB
Power Gain Flatness @ Rated PSAT	ΔGp		± 1		dB
Input Power for Rated PSAT	P _{IN}		0-3		dBm
Connector type			SMA		
Operating Voltage	V _{DC}	24		28	V
electric current		1-1.2			A

MECHANICAL SPECIFICATIONS

Cooling External HeatSink Needed (Not Supplied)
Length* Width*Height[mm] 100*33*20
Weight[Kg] 0.1
RF Connector Input N/A
RF Connector Output [2.8mm(K),SMA Female]

40dB Gain,10w,CustomizableMHz
amplifier

Solid state Broadband high power interference source

ENVIRONMENTAL SPECIFICATIONS (Design to Meet)

Module Operation Temperature	-15	60	°C
Storage Temperature Range	-30	65	°C
Relative-Humidity	N/A		
Altitude	N/A		
Vibration/Shock	N/A		

LIMITS

Input RF drive level without damage	N/A	dBm
-------------------------------------	-----	-----

DC INTERFACE CONNECTOR – [Penetrating capacitor, Male]

Pin #	Description	Specifications
A1	VCC	+28V
A2	GND	Ground

COMPLIANCE CERTIFICATIONS

XX
XX

PLOTTED AND OTHER DATA

Notes:

Datasheet: REV A.4/ 24 .06.2024



40dB Gain, 10W, Customizable MHz
amplifier

Solid state Broadband high power interference source

Product diagram



